

Models for Lithium-Ion Battery Performance and Damage

Robert M. McMeeking^{1,2,3,4}

¹Mechanical Engineering Department, University of California, Santa Barbara
California, USA

rmcm@engineering.ucsb.edu

²Materials Department, University of California, Santa Barbara, California, USA

³School of Engineering, University of Aberdeen, Aberdeen, Scotland

⁴INM – Leibniz Institute for New Materials, Campus D2 2, Saarbrücken, Germany

ABSTRACT

Models are developed for the transport of Li ions in the electrolyte of lithium ion batteries, their diffusion through storage electrode particles, and their kinetics through the surface of the particles between the electrolyte and the particles. As a consequence of the Li ion intercalating in the storage particles, their lattice swells, leading to elastic stress when the concentration of Li ions in the particles is not uniform. The models of transport are based on standard concepts for multi-component diffusion in liquids and solids, but are not restricted to dilute solutions, or to small changes in the concentration of the diffusing species. In addition, phase changes are permitted during mass transport as the concentration of lithium varies from the almost depleted state of the storage particle to one where the material is saturated with its ions. The elastic swelling and shrinkage may involve very large dilatations, which are allowed for in the formulation of the model. Thus, the models are suitable for storage particle, where the amount of Li can vary by large amounts depending on the state of charge, for staging as observed in the storage process in graphite, for the enormous swelling that takes place when silicon is used for storage, and for electrolytes in which the concentration of Li ions is high. The model is used to compute the processes of charging and discharging the battery to assess the parameters that influence the development of stress in the storage particles, and to deduce the likelihood of fracture of the storage particle material. The objective is to assess designs of porous electrode microstructures that permit rapid charging and discharging, but obviate the likelihood of fracture and other mechanical damage that limit the performance and reliability of the battery.